

# SupremeRAID™ SR-1001

**The Best Solution for NVMe RAID:** SupremeRAID™ is a software-defined RAID solution on a GPU, designed to deliver maximum SSD performance without consuming CPU cycles or creating throughput bottlenecks. Out-of-path RAID protection technology means data travels directly from the CPU to deliver unmatched flexibility, unprecedented NVMe/NVMeoF performance, and overall superior value.



SR-1001  
**For 1U  
Towers  
& Edge  
Servers**

Supports up to 8 SSDs

**Protecting NVMe-based Data From The Cloud To The Desktop:** SupremeRAID™ SR-1001 is a PCIe Gen 3 card that supports up to 8 SSDs, and delivers superior performance and flexibility for tower and edge servers, professional workstations, and gaming desktops. SupremeRAID™ SR-1001 is the perfect storage choice for engineers, videographers, telcos, CSPs, and MSPs. Its powerful performance capabilities are well suited for applications such as CAD, video editing, IoT, and gaming.

**6M**  
IOPS

**80GB/s**  
Throughput

UP TO **100%**  
SSD Performance

**80%**  
Cost Savings

**1.5x**  
Faster

	SupremeRAID™ SR-1001	Software RAID	Hardware RAID
4K Random Read	6 M IOPS	~2 M IOPS	3.9 M IOPS
4K Random Write	500 K IOPS	200 K IOPS	180 K IOPS
1M Sequential Read	80 GB/s	~9 GB/s	13.5 GB/s
1M Sequential Write	30 GB/s	2 GB/s	4 GB/s
4K Random Read (Rebuild)	1 M IOPS	Unknown	36 K IOPS
4K Random Write (Rebuild)	350 K IOPS	Unknown	18 K IOPS
CPU Utilization	None	High	None
Data Protection	RAID 0, 1, 5, 6, 10	RAID 0, 1, 5, 10	RAID 0, 1, 5, 6
NVMeoF Support	Yes	Yes	No
Flexibility	High	Limited by CPU	None
Max SSDs Supported	8	32	8

Based on Linux RAID5 with AMD EPYC 9654 96-Core Processor x 2 and KIOXIA CM7 x 24



Tower & Edge Servers, Professional Workstations, & Gaming Desktops

# SupremeRAID™ SR-1001

SR-1001  
For 1U  
Towers  
& Edge  
Servers

Supports up  
to 8 SSDs



## SR-1001 Software Specs

**Supported RAID levels:**  
RAID 0, 1, 5, 6, 10

**Max Virtual Drives  
per Drive Group:**  
8

**Max Physical Drives:** 8

**Max Drive Group Size:**  
Defined by physical drive size

**Max Drive Groups:** 4

### OS Support:

AlmaLinux 8.5, 8.6, 8.7 (Kernel 4.18)  
CentOS 7.9 (Kernel 3.10 or 4.18), 8.3, 8.4, 8.5 (Kernel 4.18)  
Debian 11.6 (Kernel 5.10)  
openSUSE Leap 15.2, 15.3 (Kernel 5.3)  
Oracle Linux 8.7 (RHCK 4.18 or UEK 5.15)  
Oracle Linux 9.1 (RHCK 5.14 or UEK 5.15)  
SLES 15 SP2, 15 SP3 (Kernel 5.3)  
RHEL 7.9 (Kernel 3.10 or 4.18), 8.3, 8.4, 8.5, 8.6, 8.7 (Kernel 4.18)  
RHEL 9.0, 9.1 (Kernel 5.14)  
Rocky Linux 8.5, 8.6, 8.7 (Kernel 4.18)  
Ubuntu 20.04.0-20.04.5 (Kernel 5.15)  
Ubuntu 22.04.0-22.04.2 (Kernel 5.15)  
Windows Server 2019 x86-64  
Windows Server 2022 x86-64  
Windows 11 x86-64

## SR-1001 Card Specs

**Host Interface:**  
x16 PCIe Gen 3.0

**Form Factor:**  
2.713" H x 6.137" L, Single Slot

**Max Power Consumption:**  
30 W

**Product Weight:**  
132.6 g



### Flexible & Future Ready

Unmatched flexibility with features like new O/S support, compression, encryption, thin provisioning, or boot drive protection can be easily added with software releases



### World Record Performance

Unprecedented NVMe/NVMeoF performance up to 6M IOPS and 80GB/s throughput with a single SupremeRAID™ card delivers the full value of your server investment



### Highly Scalable

Easily manage 8 direct attached NVMe SSDs; extend data protection without sacrificing performance with Software Composable Infrastructure



### Plug & Play

Effortless installation, no cabling or motherboard re-layout required; direct connect to SSD without PCIe switches



### Free Up CPU Resources

Offload your entire RAID computation to SupremeRAID™ to free-up CPU computing resources for 5G, AI, and AIoT applications



### Easy to Use

SupremeRAID™ doesn't rely on memory caching technology, eliminating the need for battery backup modules

“We’re perpetually impressed with the extreme storage performance SupremeRAID™ enables. For maximizing NVMe SSD performance, we haven’t seen anything on the market that can touch the SupremeRAID™ Gen5 solution. It’s fantastic, plus we’re doing the work on an inexpensive NVIDIA A2000 GPU.”

“Gone are the days of IO bottlenecks... SupremeRAID™ is the perfect platform for AI/ML, IoT, video processing, and other performance-hungry applications.”

Tower & Edge Servers, Professional Workstations, & Gaming Desktops

# SupremeRAID™ SR-1001



SR-1001  
For 1U  
Towers  
& Edge  
Servers

Supports up  
to 8 SSDs

## OPTIMAL

4K Random Read  
IOPS

4K Random Write  
IOPS

1M Sequential Read  
THROUGHPUT

1M Sequential Write  
THROUGHPUT

	Linux Environment		
	RAID 5	RAID 6	RAID 10
4K Random Read IOPS	6 M IOPS	6 M IOPS	6 M IOPS
4K Random Write IOPS	500 K IOPS	400 K IOPS	3 M IOPS
1M Sequential Read THROUGHPUT	80 GB/s	80 GB/s	80 GB/s
1M Sequential Write THROUGHPUT	30 GB/s	30 GB/s	25 GB/s

## Windows Environment

RAID 5

RAID 6

RAID 10

1.8 M IOPS

1.8 M IOPS

1.8 M IOPS

500 K IOPS

400 K IOPS

1.6 M IOPS

40 GB/s

40 GB/s

40 GB/s

8 GB/s

7 GB/s

10 GB/s

## REBUILD

4K Random Read  
IOPS

4K Random Write  
IOPS

1M Sequential Read  
THROUGHPUT

1M Sequential Write  
THROUGHPUT

	Linux Environment		
4K Random Read IOPS	1 M IOPS	1 M IOPS	4 M IOPS
4K Random Write IOPS	350 K IOPS	300 K IOPS	3 M IOPS
1M Sequential Read THROUGHPUT	10 GB/s	10 GB/s	40 GB/s
1M Sequential Write THROUGHPUT	10 GB/s	10 GB/s	25 GB/s

## Windows Environment

1.4 M IOPS

1.4 M IOPS

1.6 M IOPS

400 K IOPS

300 K IOPS

1.5 M IOPS

10 GB/s

10 GB/s

26 GB/s

7 GB/s

7 GB/s

10 GB/s

**Linux Testing Specifications:** Server: Supermicro AS-2125HS-TNR x1; CPU: AMD EPYC 9654 96-Core Processor x2; Memory: Samsung M321R2GA3BB6-CQKVS DDR5 4800 MT/s 16GB x24; NVMe SSD: KIOXIA CM7-R 3.84T KCMY1RUG3T84 x24; RAID Controller: SR-1001 x1; Linux Distro: Ubuntu 22.04.1 LTS; Kernel: 5.15.0-83-generic; Benchmarking tool: fio-3.16; SupremeRAID™ Driver version: 1.5.0-670.g03a5380c.001gcf5e69d8

**Windows Testing Specifications:** Server: Supermicro SYS-220U-TNR x1; CPU: Intel Xeon Gold 6338 CPU @ 2.00GHz x2; Memory: SK Hynix HMA82GR7CJR8N-XN 16GB DDR4-3200 RDIMM x16; NVMe Drive: Solidigm D7-P5510 x16; RAID Controller: SR-1010 x1; OS: Windows 2022, Driver Version: 1.2.3-185; SupremeRAID™ driver version: 1.2.3; max performance based on a drive group with 8 physical drives and 2 virtual drives

## SupremeRAID™: Protecting NVMe-based Data From The Cloud To The Desktop

Graid Technology Inc. is headquartered in Silicon Valley, with an R&D center in Taipei, Taiwan. Our leadership is composed of a dedicated team of experts with decades of experience in the SDS, ASIC and storage industries. Learn more at [graidtech.com](http://graidtech.com).

Learn More: [info@graidtech.com](mailto:info@graidtech.com)

5201 GREAT AMERICA PARKWAY, SUITE 320 | SANTA CLARA, CA 95054

 Graid Technology Inc.

Copyright © 2021–2024 Graid Technology Inc. All Rights Reserved. SupremeRAID™ is among the trademarks of Graid Technology Inc. and/or its affiliates in the United States, certain other countries, and/or the EU. For more information, please visit [www.graidtech.com](http://www.graidtech.com). Graid Technology Inc. reserves the right to make changes without further notice to any products or data described herein. Information provided by Graid Technology Inc. is believed to be accurate. However, Graid Technology Inc. does not assume any liability arising from the use of any application or product described herein, neither does it convey any license under its patent rights nor the rights of others.



20240124